

The perfect tree climbing sit harness for professionals looking for maximum versatility combined with exceptional comfort. Designed to be used in combination with the Tree Access SRT Chest progression chest part and the Turboknee System ascender for SRT. The sturdy build meets European CE EN, ANSI and ASTM standards.

The harness offers many connection possibilities for efficient organization, work and positioning: two mobile attachment bridges made of rope reinforced with tubular webbing; side loops at the ends of the lower bridge and aluminum alloy ring on the upper bridge; double ventral attachment point, one metallic and one textile; two side rings on the belt; numerous gear loops and slots for the Kilo gear carabiner.

The comfort is incomparable: adjustable connection of the mobile bridges to the belt allow the worker to adjust the position of suspension; ergonomic padding with variable thickness; lowprofile STS ANSI buckles on the leg loops.

Equipped with NFC TRACK tag for digital identification.




2 sizes.

2022 UPDATE: new name (TREE ACCESS ST instead of TREE ACCESS ANSIST).




TREE ACCESS STO + TREE ACCESS SRT CHEST



Ref.	Product name	Size	Weight		Waist 	Legs 	CE		ANSI	ASTM	Attachment points 
			g	oz	B (cm)	C (cm)	EN 358	EN 813	Z133:2017	F887	
3125	TREE ACCESS ST	S-L	2230	78.7	80-120	50-65	•	•	•	•	
		L-XXL	2300	81.2	90-135	60-75	•	•	•	•	

- 1 Two mobile attachment bridges made of rope reinforced with tubular webbing; side loops at the ends of the lower bridge and aluminum alloy ring on the upper bridge.
- 2 Aluminium alloy attachment ring, d.45xD.69 mm, 30 kN.
- 3 Bridge system is manufactured from 10.5 mm semi-static rope covered with tubular webbing for the best durability. Two loops on the ends of the bridge create extra points for positioning.
- 4 Stainless steel connection rings with hexagonal screws for replacements of the rope webbing.
- 5 Ventral attachment point.
- 6 Two side rings on the belt
- 7 Numerous gear loops and slots for the Kilo gear carabiner.
- 8 Adjustable connection of the mobile bridges to the belt allow the worker to adjust the position of suspension
- 9 Ergonomic padding with variable thickness.
- 10 Patented STS ANSI automatic buckles on the leg loops.
- 11 Patented "Sicura" buckles for fastening the "Access Swing".
- 12 Back leg-loops connection webbings adjustable in length with new buckles.
- 13 One gear ring on each leg-loop.
- 14 Elastic webbing for "First Aid Kit" fastening.
- 15 Webbing loop for "Access Swing" fastening when not in use.
- 16 Three webbing loops for connect the chest part (TREE ACCESS SRT CHEST Ref.3126)
- 17 Equipped with NFC TRACK tag for digital identification.



TREE ACCESS SRT CHEST

- ❶ Dedicated attachment points for the Turboknee System.
- ❷ Numerous loops for secondary connections.
- ❸ Padded shoulders for all day comfort. Padding is color differentiated for left and right.

WARNING:

The Tree Access SRT Chest is a climbing aid/accessory harness, it must never be used to for life support or safety functions.




Turboknee System
3127
Sold separately



BLACK
colour
(Left)

RED
colour
(Right)

Ref.	Product name	Size	Weight		Height 
			g	oz	D (cm)
3126	TREE ACCESS SRT CHEST	One size	265	9.4	55-85

ACCESS RING

2046 34 mm
204601 45 mm

ROPE ACCESS, TREE CLIMBING

Aluminum alloy connection ring that is useful for the connection of various fall arrest components and can be inserted into the mobile bridge system of the Tree Access series harnesses. Available in two color-coded sizes with different diameters.



Ref.	Product name	Weight		Diameter mm	Strength kN	CE	ANSI Z359.12
		g	oz				
2046	ACCESS RING 34 mm	34	1.2	Int. 34 - Ext. 54	24	•	
204601	ACCESS RING 45 mm	59	2.1	Int. 45 - Ext. 69	30	•	

TREE ACCESS EVO/ST/XT BRIDGE WITH SIDE LOOPS

216403 32 cm
216404 37 cm
216405 42 cm

TREE CLIMBING

Mobile attachment bridge for all Tree Access harnesses. Equipped with side attachment loops for positioning. Manufactured from 10.5 mm semi-static rope covered with tubular webbing for the best durability. Available in three lengths: 32 cm, 37 cm and 42 cm.



Ref.	Weight	
	g	oz
216403 - 32 cm	65	7.0
216404 - 37 cm	70	8.1
216405 - 42 cm	75	8.3

TREE ACCESS EVO/ST/XT BRIDGE WITH SIDE LOOPS + GYRO

216406 32 cm
216407 37 cm
216408 42 cm

TREE CLIMBING

Mobile attachment bridge equipped with the Gyro3 triple swiveling device for maximum freedom of movement. Equipped with side attachment loops for positioning. Compatible with all Tree Access Evo harnesses. Manufactured from 10.5 mm semi-static rope covered with tubular webbing for the best durability. Available in three lengths: 32 cm, 37 cm and 42 cm.



Ref.	Weight	
	g	oz
216406 - 32 cm	225	7.9
216407 - 37 cm	230	8.1
216408 - 42 cm	235	8.3

TREE ACCESS EVO/ST/XT BRIDGE NO SIDE LOOPS

216409 32 cm
216410 37 cm

TREE CLIMBING

Mobile attachment bridge for all Tree Access harnesses. Simplified version without side loops. Manufactured from 10.5 mm semi-static rope covered with tubular webbing for the best durability. Available in two lengths: 32 cm and 37 cm. Puente móvil de repuesto para los arneses Tree



Ref.	Weight	
	g	oz
216409 - 32 cm	45	1.6
216410 - 37 cm	50	1.8

TREE ACCESS WEBBING BRIDGE

216401 25 cm

216402 30 cm

TREE CLIMBING

Webbing replacement mobile attachment bridge. Compatible with the Tree Access Evo harness.
Available in two lengths: 25 cm and 30 cm.



Ref.	Weight	
	g	oz
216401 - 25 cm	30	1.1
216402 - 30 cm	35	1.2

TREE ACCESS SHACKLE

3162

Replacement stainless steel shackle, compatible with all Tree Access series harnesses.



Ref.	Product name	Weight	
		g	oz
3162	TREE ACCESS SHACKLE	120	4.2

TREE ACCESS SIDE WEBBINGS

3267

Pair of replacement adjustable side webbings, compatible with all Tree Access series harnesses.



Ref.	Product name	Weight	
		g	oz
3267	TREE ACCESS SIDE WEBBINGS	46	1.6

C.A.M.P. presents in this catalog a **complete solution for the digital management of PPE**, both for allocation to users and for periodic inspections: the **NFC TRACK hardware tags on the products** work seamlessly with the **G.T.S. - Gear Tracking System software** to make the system very intuitive and easy to use.

NFC TRACK chips are installed on many C.A.M.P. products (harnesses, helmets, Retexo lanyards). They **can also be attached directly on any PPE** by the user, so that the user can assign the PPE data to the chip by means of the C.A.M.P. G.T.S.

NFC (Near Field Communication) technology is now present on most smartphones and used every day for smart payments. Today, it also represents the future for the individual identification of products.

The **HF RFID** (High Frequency Radio Frequency Identification) communication system on which NFC is based allows the C.A.M.P. NFC TRACK to be easily read using any latest generation smartphone or for professionals using a PC reader.



NFC TRACK chip installed!



- G.T.S. - GEAR TRACKING SYSTEM

G.T.S. allows professionals to easily manage PPE both via the smartphone app (available on Play Store and Apple Store) and from a PC via the web app.

Two different packages allow for carrying out periodic inspections and also for managing the company allocation of PPE to its employees.

The database of **G.T.S.** includes the **technical information of all C.A.M.P. products** for work at height and a **large number of other products** posted by other users of the community with publicly available information.

